OFFICE OF THE MARION COUNTY SURVEYOR SECTION RECORD CORNER SECTION <u>29</u> TOWNSHIP <u>17</u> RANGE <u>4</u> DATE: <u>11-6-08</u> PARTY CHIEF: Wilcoxen 75th 7500N 4000 CREW: _ TYPE OF MARKER: Harrison METHOD OF ESTABLISHMENT: County 9-12-04 IN. S.P.C. E ZONE NAD '83 17042905 NAME: 515445.0060(m) N: E: 63082.3705(m) NOTE: This corner position represents a title corner and may not necessarily be in the position of the 1. Record corner. 75th Street 2. 75th Street Section Line 3. Dean

A survey by Fatout 8-24-1880 called follwing witness: 30" sugar N 77 1/4 E 189 links; a balsam fir N 10 1/4 W 177 links per Washington Township Legal Survey Book pg. 81. Hankins 2-25-59 called a railroad spike. McLand 4-30-71 called the same. McLand 6-16-72 called a PK nail. Wilcoxen 8-26-86 called a flagged rebar. Greene 4-3-87 called same. Wilcoxen excavated 9-16-93 and a bent rebar found at surface. Set Harrison. Re-tied 7-19-99 by Kiste. Re-tied 9-12-04 by Wilcoxen. Re-tied 11-6-08 by Wilcoxen raised 4".

DESCRIPTION

17042905

RFF. DISTANCE

INC. I	DIOTHNOL	DESCRIPTION
1.	59.10	Rebar set @ NW edge of large granite stone
2.	39.91'	Mag nail w/bw N PwP#1-242 12"up
3.	71.00'	Rebar leaning N by NF corner of concrete headwall
4.	23.02'	Mag nail w/bw N PwP#252-242 12"up